## CORRECTED VERSION

## (19) World Intellectual Property Organization

International Bureau



## 

(43) International Publication Date 15 July 2004 (15.07.2004)

PCT

(10) International Publication Number WO 2004/059934 A1

(51) International Patent Classification7: H04Q 7/30

H04L 27/233,

(21) International Application Number:

PCT/IB2002/005613

(22) International Filing Date:

24 December 2002 (24.12.2002)

(25) Filing Language:

Italian

(26) Publication Language:

English

- (71) Applicants (for all designated States except US): PIRELLI & C. S.p.A. [IT/IT]; Via Gaetano Negri, 10, I-20123 Milano (IT). TELECOM ITALIA S.P.A. [IT/IT]; Piazza degli Affari, 2, I-20121 Milano (IT).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): BUSCAGLIA, Flavio [IT/IT]; Telecom Italia Lab S.p.A., Via G. Reiss Romoli, 274, I-10148 Torino (IT). BERNASCONI, Valerio [IT/IT]; Telecom Italia Lab S.p.A., Via Reiss Romoli, 274, I-10148 Torino (IT).


- (74) Agents: BATTIPEDE, Francesco et al.; Pirelli S.p.A., Viale Sarca, 222, I-20126 Milano (IT).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Published:

with international search report

(48) Date of publication of this corrected version:

10 September 2004



signal associated with a first band and at least one adjacent signal of said plurality associated with a second band adjacent to that of the first signal; a processing stage (BP-IP, DEM, AD-1) for generating from the first digital signal at a first sampling frequency, this first digital signal including a suseful spectral content of the first signal and an interfering spectral content associated with said adjacent signal; a digital filter (DLPF) for processing the first digital signal, attenuating the interfering spectral content, and for providing a filtered digital signal including at least part of said useful spectral content, sampled at a second sampling frequencx less than the first sampling frequency and an electro-optical converter (E/O-A) for generating from said filtered digital signal electromagnetic radiation to be transmitted on a waveguide (F-up1).

BEST AVAILABLE COPY

